

Native IP Device

Gateways connect to your IP network and provide a 'line out' input to existing amplifiers

Prioritised Audio

The AUG3001-IP supports up to 9 levels of priority for audio announcements for selective muting.

Power over Ethernet

Single cable deployment, powered from IEEE802.3af Power over Ethernet

Flex I/O

Features 4 Flex Inputs and 4 Flex outputs. Each Flex I/O is configurable via the browser interface, providing flexible configuration options for attached I/O

IP Integration

Netgenium's PolicyServer provides automated announcements along with seamless integration with Cisco IP Telephony and Milestone Xprotect Smart Client.

NGx console applications provide paging from Windows pc's.



AUG3001-IP

Migrate a traditional audio Public Address system to IP with Netgenium IP Audio Gateways and make paging announcements via an IP Telephone system or PC application.

The IP Audio Gateway offers gateway interoperability between Cisco Call Manager for Audio announcements using G.711 audio, and the ability to 'pipe' background music from a multicast audio source.

Integrate Public Address with Netgenium's PolicyServer and NGx consoles applications and make targeted paging announcements to an individual or group of individuals within a specific 'Zone' in your building.

Technical Data

Model No:
AUG3001-IP

Connectivity:
1 No. 10/100 Base TX Ethernet RJ45

Supported Protocols:
Cisco Call Manager Skinny
SIP 2.0 (peer and proxy)

Supported Codecs:
G711 uLaw ,G711 ALaw, PCM
Wav 11.025 Khz, Wav 22.05 Khz, Wav 44.1 Khz, Wav 48 Khz

Onboard I/O:
No 4 Flex Inputs (Requires Digital 0v contact)
No4 Flex Outputs (12V switched –ve)
Flex I/O can be used for local announcements, IP events and PolicyServer control

Power Supply:
Power over Ethernet IEEE802.3af

Dimensions:
1RU Rack Mountable 330mm depth

Weight:
700g

Environment:
Environment Temperature -5° C to +40° C
Humidity 0-95% rh non-condensing