

Native IP Device

Intercoms connect to your IP network.
Simple to install and easily configured with a
Web browser

Power over Ethernet

Single cable deployment. Powered from
IEEE802.3af PoE

I/O

Features voltage free relay contacts.
The contacts can be activated by
incoming event or DTMF tones from a
telephone handset.

IP Integration

IP Intercoms integrate with IP Telephony to
extend the functionality of your telephone
system

IPT Integration

The ICP0210-IP supports SIP and
SCCP call control protocols.



ICP0210-IP

Securely manage entry to your building with Netgenium's IP audio intercom panel. A device capable of integrating with the existing infrastructure for ease of use and installation

The ICP0210-IP is a native IP device, providing dynamic communication between a door entry point and one or more telephone handsets or pc's on the network.

Control doors remotely from the telephone handset using DTMF, soft buttons or speed dials.

Supports SIP registration and peer to peer operation as well as Cisco SCCP call control protocol.



ICP0210-IP

Audio Intercom Panel

Technical Data

Model No:
ICP0210-IP

Connectivity:
1 No. 10/100 Base TX Ethernet RJ45

Supported Protocols:
Cisco Call Manager Skinny
SIP 2.0 (peer and proxy)

Supported Codecs:
G711 uLaw

Onboard I/O:
No 1 Flex Inputs (Requires Digital 0v contact)
NO/NC Clean Contact (Triggered by incoming event or DTMF)

Power Supply:
Power over Ethernet IEEE802.3af

Dimensions:
Stainless Steel (brushed) plate 130mm(W) x 215mm(H) x 35mm(D)

Weight:
2 Kg

Environment:
Environment Temperature -5° C to +40° C
Humidity 0-95% rh non-condensing



IP Devices
Access, Security, Audio & Lighting Control

18A White Rose Way
Follingsby Park
Gateshead
Tyne & Wear
NE10 8YX

T: +44 (0) 845 9011148
F: +44 (0) 845 9011149
E: sales@netgenium.co.uk
W: www.netgenium.co.uk

©Netgenium Systems 2014