

Native IP Device

Speakers connect to your IP network. Simple to install and easily configured with a web browser.

Power over Ethernet

Single cable deployment. Onboard Audio amplifier delivering up to 7W with IEEE802.3af.

Prioritised Audio

The ASP7201-IP supports up to 9 levels of priority for audio announcements for selective muting.

Flex I/O

Features 4 Flex Inputs and 4 Flex Outputs. Each Flex I/O is configurable via the browser interface, providing flexible configuration options for attached I/O.

IP Integration

Netgenium's PolicyServer provides automated announcements along with seamless integration with Cisco Skinny and SIP IP Telephony and Milestone Xprotect Smart Client.



ASP7201-IP

Deploy an audio PA system over an IP Network with Netgenium IP Speakers and make paging announcements via an IP Telephone system or PC.

The IP Speaker offers interoperability between Cisco Call Manager for Audio announcements using G.711 audio, and the ability to 'pipe' background music from a multicast audio source.

Integrate speakers with Netgenium's PolicyServer and NGx consoles applications and make targeted paging announcements to an individual or group of individuals within a specific 'Zone' in your building.

By utilising Power over Ethernet, the speaker is easy to deploy and manage. Features such as mute and volume are controlled via software.



ASP7201-IP

IP Dc9 Ceiling Speaker

Technical Data

Model No: ASP7201-IP

Connectivity: 1 No. 10/100 Base TX Ethernet RJ45

Supported Codecs: G711 uLaw, G711 ALaw, PCM Wav 11.025 Khz, Wav 22.05 Khz, Wav 44.1 Khz, Wav 48 Khz

Onboard I/O: No 4 Flex Inputs (Requires Digital 0v contact) No 4 Flex Outputs (12V switched -ve) Flex I/O can be used for local announcements, IP events and PolicyServer control

Power Supply: Power over Ethernet IEEE802.3af

Mechanical Case diameter 203mm Net weight 700g



Vertical text on the right side of the footer area.

Contact information: T: +44 (0) 191 6030000 E: sales@netgenium.co.uk W: www.netgenium.co.uk